

TECHNICAL SPECIFICATIONS

ADT-ALUFTS101

10.1" ALUMINIUM FRAMED TOUCH SCREEN



OVERVIEW

A standalone product finished to a high standard where the touch screen cover glass is enclosed on the edges by an aluminium bezel.

This edge detail protects the cover glass and encloses the touch monitor. Units can be supplied with a stand, or with as standard with rear VESA points for attachment into retail designs.

Optional OPS allows customers CMS or application to reside on the unit and be serviceable via the removable computing module.

KEY FEATURES

- Touch Monitor frame creates perfect edge between touch panel and housing
- Optional Open Pluggable Specification (OPS) for CMS / Applicatio
- Projective capacitive touch with up to 10 concurrent points
- Differing surface treatments including AG to reduce fingerprints
- Large range of sizes from 10.1" to 65"

10.1" Aluminium Framed Touch Screen

Panel	
Active Display Area	216.96 (W) x 135.6 (H) mm
Backlight	LED
Resolution	1280 x 800 (16:10)
Brightness	LED: 350nits / Display 301 cd/m2 with PCAP touchscreen
Contrast Ratio	800:1
Viewing Angle	85/85/85/85
Display Colours	262k

Mechanical Structure	
Dimensions	249.5 x 168.37 x 29.00mm
Net Weight	3.5 kg
Ingress Protection	IP65
Glass Material	1.1mm strengthened glass
MTBF	50,000 hours
Operating Temperature	0°C - 40°C
Power Consumption	Max 10w – Standby: < 0.5w
Mounting	Standard VESA mounting bracket

Connectivity	
VGA	1 x VGA
DVI	1 x DVI
HDMI	1 x HDMI
Audio	1 x 3.5mm jack
Touch	1 x touch interface USB

Dimensions (CAD)

